



AMERICAN MINING CONGRESS TURNOUT DATA

Turnout Data for 48-in. Gage (continued) Heavy Rail – 70-lb to 100-lb rail, inclusive

American Mining Congress Standards

No.	Angle	Frog					Switch					Actual Lead	Closure Rails			
		Type	Rail Weight	Point	Actual Toe Length	Length	Angle	Point	Heel Spread	Vertex Distance	Curved			Straight Length		
											Radius		MO		Length	
3	18°55'29"	Cast	70 to 80	1/2"	9-1/2"	7'6"	3°35'00"	3/8"	6"	6"	24'1"	58'0"	6-13/16"	16'2-13/16"	15'9-1/2"	
		Cast	85 to 100	1/2"	11"	7'6"	3°44'35"	3/8"	6-1/4"	6"	23'10-1/2"	56'10-5/16"	6-11/16"	15'10-13/16"	15'5-1/2"	
		RBF	70 to 80	1/2"	31"	7'6"	3°35'00"	3/8"	6"	6"	24'1"	58'0"	5-3/8"	14'5-1/4"	14'0"	
		RBF	85 to 100	1/2"	31"	7'6"	3°44'35"	3/8"	6-1/4"	6"	23'10-1/2"	56'10-5/16"	5-3/8"	14'2-13/16"	13'9-1/2"	
4	14°15'00"	Cast	70 to 80	1/2"	12-9/16"	7'6"	3°35'00"	3/8"	6"	6"	28'10"	107'0"	5-15/16"	20'7-9/16"	20'3-1/2"	
		Cast	85 to 100	1/2"	14-5/8"	7'6"	3°44'35"	3/8"	6-1/4"	6"	28'6-1/4"	105'3-3/4"	5-3/4"	20'1-3/4"	19'9-5/8"	
		RBF	70 to 80	1/2"	40"	7'6"	3°35'00"	3/8"	6"	6"	28'10"	107'0"	4-3/4"	18'4-1/16"	18'0"	
		RBF	85 to 100	1/2"	40"	7'6"	3°44'35"	3/8"	6-1/4"	6"	28'6-1/4"	105'3-3/4"	4-5/8"	18'0-3/8"	17'8-1/4"	
5	11°25'16"	Cast	70 to 80	1/2"	15-11/16"	10'0"	2°41'12"	3/8"	6"	8"	37'1"	167'0"	6-1/8"	26'0-1/2"	25'9-5/16"	
		Cast	85 to 100	1/2"	18-3/16"	10'0"	2°48'23"	3/8"	6-1/4"	8"	36'9-5/16"	164'3-1/8"	5-15/16"	25'6-3/8"	25'3-1/8"	
		RBF	70 to 80	1/2"	42-1/2"	10'0"	2°41'12"	3/8"	6"	8"	37'1"	167'0"	5-1/16"	23'9-3/4"	23'6-1/2"	
		RBF	85 to 100	1/2"	42-1/2"	10'0"	2°48'23"	3/8"	6-1/4"	8"	36'9-5/16"	164'3-1/8"	5-1/16"	23'6-1/16"	23'2-3/16"	
6	9°31'38"	Cast	70 to 80	1/2"	18-13/16"	10'0"	2°41'12"	3/8"	6"	8"	41'6"	248'0"	5-1/2"	30'1-15/16"	29'11-3/16"	
		Cast	85 to 100	1/2"	21-13/16"	10'0"	2°48'23"	3/8"	6-1/4"	8"	41'1-1/2"	244'9-5/16"	5-3/8"	29'6-9/16"	29'3-11/16"	
		RBF	70 to 80	1/2"	45"	10'0"	2°41'12"	3/8"	6"	8"	41'6"	248'0"	4-3/4"	27'11-3/4"	27' 9"	
		RBF	85 to 100	1/2"	45"	10'0"	2°48'23"	3/8"	6-1/4"	8"	41'1-1/2"	244'9-5/16"	4-11/16"	27'7-3/8"	27'4-1/2"	
7	8°10'16"	Cast	70 to 80	1/2"	21-13/16"	10'0"	2°41'12"	3/8"	6"	8"	45'10-15/16"	349'4-7/16"	5-1/16"	34'3-5/16"	34'1"	
		Cast	85 to 100	1/2"	25-7/16"	10'0"	2°48'23"	3/8"	6-1/4"	8"	45'2-1/4"	346'4-1/4"	4-13/16"	33'3-3/16"	33'0-13/16"	
		RBF	70 to 80	1/2"	56-1/2"	10'0"	2°41'12"	3/8"	6"	8"	45'10-15/16"	349'4-7/16"	4-1/4"	31'4-3/4"	31'2-7/16"	
		RBF	85 to 100	1/2"	56-1/2"	10'0"	2°48'23"	3/8"	6-1/4"	8"	45'2-1/4"	346'4-1/4"	4-1/16"	30'8-1/8"	30' 5-3/4"	
8	7°9'10"	Cast	70 to 80	1/2"	25-1/16"	15'0"	1°47'27"	3/8"	6"	12"	58'6-5/16"	435'10-3/4"	5-5/8"	41'7-1/2"	41'5-1/4"	
		Cast	85 to 100	1/2"	29-1/16"	15'0"	1°52'14"	3/8"	6-1/4"	12"	57'8-7/16"	429'8-7/16"	5-3/4"	40'5-3/8"	40'3-3/8"	
		RBF	70 to 80	1/2"	61"	15'0"	1°47'27"	3/8"	6"	12"	58'6-5/16"	435'10-3/4"	5-1/16"	38'7-9/16"	38'5-5/16"	
		RBF	85 to 100	1/2"	61"	15'0"	1°52'14"	3/8"	6-1/4"	12"	57'8-7/16"	429'8-7/16"	5"	37'9-7/16"	37'7-7/16"	

Note: RBF denotes "Rigid Bolted Frog."

Turnout Data for 56-1/2-in. Gage Light Rail – 20-lb to 60-lb ASCE rail, inclusive

American Mining Congress Standards

No.	Angle	Frog					Switch					Actual Lead	Closure Rails			
		Type	Rail Weight	Point	Actual Toe Length	Length	Angle	Point	Heel Spread	Vertex Distance	Curved			Straight Length		
											Radius		MO		Length	
2	28°04'21"	Cast	20 to 60	1/4"	6-11/16"	3'6"	6°19'20"	3/8"	5"	4"	16'7"	33'0"	8-1/16"	13'4"	12'6-1/4"	
		WPF	20 to 30	1/4"	17"	3'6"	6°19'20"	3/8"	5"	4"	16'7"	33'0"	7-1/16"	12'5-3/4"	11'8"	
		WPF	40 to 60	3/8"	20"	3'6"	6°19'20"	3/8"	5"	4"	16'7"	33'0"	6-3/4"	12'2-3/4"	11'5"	
2-1/2	22°37'12"	Cast	20 to 60	1/4"	8-1/4"	5'0"	4°25'15"	3/8"	5"	5"	22'0"	51'0"	8-7/16"	16'11-1/4"	16'3-3/4"	
		WPF	20 to 30	1/4"	16-1/2"	5'0"	4°25'15"	3/8"	5"	5"	22'0"	51'0"	7-3/4"	16'3"	15'7-1/2"	
		WPF	40 to 60	3/8"	20"	5'0"	4°25'15"	3/8"	5"	5"	22'0"	51'0"	7-1/2"	15'11-1/2"	15'4"	
3	18°55'29"	Cast	20 to 60	1/4"	8-3/8"	5'0"	4°25'15"	3/8"	5"	5"	25'0"	76'0"	7-3/4"	19'10"	19'3-1/2"	
		WPF	20 to 30	1/4"	16-1/2"	5'0"	4°25'15"	3/8"	5"	5"	25'0"	76'0"	7-1/4"	19'1-3/4"	18'7-1/2"	
		WPF	40 to 60	3/8"	24"	5'0"	4°25'15"	3/8"	5"	5"	25'0"	76'0"	6-3/4"	18'6-1/2"	18'0"	
4	00°15'00"	Cast	00 to 00	1/4"	11-1/16"	5'0"	4°25'15"	3/8"	5"	5"	30'4"	140'0"	6-9/16"	24'9-3/4"	24'5"	
		WPF	00 to 00	3/8"	27"	5'0"	4°25'15"	3/8"	5"	5"	30'4"	140'0"	5-15/16"	23'6"	23'1"	
4	14°15'00"	Cast	20 to 60	1/4"	11-1/16"	7'6"	2°56'44"	3/8"	5"	8"	34'10"	132'0"	8-3/16"	26'9-1/2"	26'4-3/4"	
		WPF	40 to 60	3/8"	27"	7'6"	2°56'44"	3/8"	5"	8"	34'10"	132'0"	7-11/16"	25'6"	25'1-1/4"	
5	11°25'16"	Cast	20 to 60	1/4"	13-13/16"	7'6"	2°56'44"	3/8"	5"	8"	40'7"	212'0"	7-3/8"	32'3"	31'11-1/4"	
		WPF	40 to 60	3/8"	30"	7'6"	2°56'44"	3/8"	5"	8"	40'7"	212'0"	6-3/4"	30'10-3/4"	30'7"	
6	9°31'38"	Cast	20 to 60	1/4"	16-9/16"	7'6"	2°56'44"	3/8"	5"	8"	45'10"	316'0"	6-9-16"	37'2-3/4"	36'11-1/2"	
		WPF	40 to 60	3/8"	36"	7'6"	2°56'44"	3/8"	5"	8"	45'10"	316'0"	6"	35'7-1/4"	35'4"	
6	9°31'38"	Cast	20 to 60	1/4"	16-9/16"	10'0"	2°12'32"	3/8"	5"	10"	50'7"	302'0"	7-3/4"	39'5-1/2"	39'2-1/2"	
		WPF	40 to 60	3/8"	36"	10'0"	2°12'32"	3/8"	5"	10"	50'7"	302'0"	7-1/8"	37'10-1/4"	37'7"	

Note: WPF denotes "Welded Plate Frog."